



>>>

CODE	DIM dxg [mmxin]	D [mm]	L [mm]	I [mm]	H [mm]	PN [bar]
1004051005001	*50x1"1/4	96	131	100	22	16
1004051006001	*50x1"1/2	96	132	100	23	16
1004051007001	*50x2"	96	137	100	22	16
1004064005001	*63x1"1/4	115	159	121	23	16
1004064006001	*63x1"1/2	115	160	121	28	16
1004064007001	*63x2"	115	165	121	22	16
1004064008001	*63x2"1/2	115	168	121	23	16
1004076007001	*75x2"	129	182	137	28	16
1004076008001	*75x2"1/2	129	187	137	33	16
1004076009001	*75x3"	129	187	137	33	16
1004091007001	*90x2"	155	190	152	26	16
1004091008001	*90x2"1/2	155	195	152	33	16
1004091009001	*90x3"	155	195	152	33	16
1004091010001	*90x4"	155	204	152	42	16
1004111009001	*110x3"	183	263	204	40	16
1004111010001	*110x4"	183	263	204	43	16

\* The threaded end is reinforced with a stainless steel ring

\* Die Gewindeöffnung ist mit einem Ring aus rostfreiem Stahl verstärkt

\* Резьбовой вход укреплен кольцом из н/ж стали